

unbalanced pro audio patch cable coaxial - flexible -PVC

- 0.22 mm² conductor cross section (AWG 24)
- extremely flexible
- bare copper spiral shield
- small outer diameter, 4.0 mm

PVC

Ce câble économique et asymétrique peut être employé partout où il y a de faibles sollicitations mécaniques, par ex. câblage interne du rack d'appareils de niveau de ligne. Blindé par blindage en spirale en cuivre très étanche, il peut aussi être utilisé à proximité de forts champs de dispersion.

design

cond. construction	stranded bare copper, 7x 0.20 mm
cond. cross section	0.22 mm²
insulation	polyethylene (PE)
shielding	bare copper spiral shield
outer jacket	PVC, matt
outer diameter	4.0 mm

electric

conductor resistance	< 85 Ω/km
capacitance	
cond. / shield	130 pF/m
insulation resistance	> 1 GΩ x km

mechanical & thermal characteristics

operating temperature	-25°C / +70°C
min. bending radius	
installed	4x overall diametre
mobile use	8x overall diameter
no hazardous substances	acc. to EU directivo RoHS 2011/65/EU from 08.06.2011
CE conformity	acc. to EU directivo LVD 2006/95/EG

order code	cable color	weight kg/m	standard lengths m
IY104SW	black	0.02	30 / 50 / 100 / 200 / 300 / 500

technical specifications are subject to change

KLOTZ AIS GmbH
Johann-Sebastian-Bach-Str. 36
85591 Vaterstetten / Munich
Tel.: +49.(0)8106.308.0
Fax: +49.(0)8106.308.101
info@klotz-ais.com
klotz-ais.com