



MSR Hot Restrike

MSR 1200 HR 1CT/2

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Operating and Electrical	
Cap-Base	G38	Power Consumption	1,200 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	13.5 A
Life to 50% Failures (Nom)	1,000 hour(s)		
Light Technical		Controls and Dimming	
Color Code	- [Not Specified]	Dimmable	Yes
Luminous Flux	103,000 lm		
Chromaticity Coordinate X (Nom)	323	Mechanical and Housing	
Chromaticity Coordinate Y (Nom)	328	Net Weight (Piece)	0.275 kg
Correlated Color Temperature (Nom)	6000 K		
Luminous Efficacy (Rated) (Min)	75 lm/W	Product Data	
Luminous Efficacy (rated) (Nom)	88 lm/W	Order product name	MSR 1200 HR 1CT/2
Color rendering index (CRI)	95	Full product name	MSR 1200 HR 1CT/2
Arc Length O (Nom)	10.0 mm	Full product code	872790092606400
		Order code	928105005114
		Material Nr. (12NC)	928105005114

MSR Hot Restrike

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900926064
Numerator - Packs per outer box	2


EAN/UPC - Case	8727900926071
----------------	---------------

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 1200	40 mm	10.0	106	108 mm	107	200	67 mm	65	63 mm
HR 1CT/2		mm	mm		mm	mm		mm	

Photometric data



Spectral Power Distribution Colour - MSR 1200 HR 1CT/2

